



# rad-DX™

Wireless Mesh Networked Radiation Detector

## FEATURES

D-tect SensorNet (mesh network) equipped - automatic connections between all Rad-DXs within 1000 m

Integrates with a local network via encrypted Wi-Fi or Ethernet

Control and monitor on a smartphone, tablet or PC

Integrated floorplan design shows the radiation source

Mounts on standard electrical junction boxes

Blends into public areas - small, lightweight, and innocuous

IP65 rated (sealed against dust and rain)

Radiation detection in less than 1 second


Sensitive Dose Rate and Total Dose measurement and recording

## RADIATION DETECTION

Rad-DX products are part of D-tect System's growing line of radiation detection products that can communicate with one another using a mesh network as well as Wi-Fi and Ethernet. Combined with this flexible communication, a sensitive scintillation detector allows the Rad-DX to detect even faint sources of radiation within 1 second.

## MESH COMMUNICATION

The Rad-DX operates on the new D-tect SensorNet - an automatic communication network that allows users to monitor a full network of Rad-DXs as long as they are in range of a single Rad-DX system! The Rad-DX units will automatically form an intelligent, self-healing mesh network, allowing them to be constantly connected to each other as well as to the user network.



## INTUITIVE INFORMATION DISPLAYS

Monitor Rad-DXs on floor plan or map displays providing an intuitive understanding of the location of a radioactive source. Dose rates can be viewed in multiple graph formats.

# rad-DX™

## SPECIFICATIONS

<b>Radiation Detector</b>	Large cesium iodide scintillation (Csl) crystal
<b>Communication</b>	D-tect SensorNet, Wi-Fi, Ethernet, USB
<b>Power</b>	120/240V AC, 50/60Hz
<b>Detection Speed</b>	Less than 1 second
<b>Energy Range</b>	59 keV - 2 MeV
<b>Battery Back-Up</b>	Lithium Ion
<b>Dose Rate Range</b>	1 $\mu$ Rem/hr - 100 mRem/hr (.01 $\mu$ Sv/hr - 1 mSv/hr)
<b>Dose Rate Linear Error</b>	+/-10%
<b>Units</b>	mrem/hr, $\mu$ Sv/hr, cps
<b>Dimensions</b>	5.97" x 5.92" x 1.75" (15.2 cm x 15 cm x 4.4 cm)
<b>Weight</b>	Non-display version: 0.5 lb (0.2 kg) Display version: 0.65 lb (0.3 kg)
<b>Environment</b>	IP65 rated for indoor/outdoor operation; NEMA Enclosure available for added environmental protection



## CONTROL & MONITOR WITH A SMARTPHONE/TABLET/PC

Each Rad-DX can be controlled and monitored by a PC on the network or across the internet on any Tablet or remote PC. 128-bit encryption protected. Monitoring can be real-time or past event logs can be reviewed.

## SYSTEM CONFIGURATION OPTIONS

The DX View is a PC application used to monitor and configure Rad-DX detectors. Multiple detectors can be configured as long as one detector is connected to the PC directly and the other detectors are configured to communicate via the mesh network.

The DX Dashboard is a web server application. This software can also be used to monitor and control a Rad-DX network. It runs on either the D-tect Cloud server or the DX Network Assistant (if installed at your facility). Using the DX Dashboard, you can access your Rad-DX network using any web-enabled device (smartphones, tablets, PCs).

